



AD-AZ (AQUAZINGA Additive)

AD-AZ is a dedicated additive developed for use with AQUAZINGA. When added to AQUAZINGA, AD-AZ reduces the risk of cracking caused by overapplication or excessive film thickness, particularly at edges and sharp geometries. In addition, it improves the coating's tolerance to minor surface contamination by oil or paint residues, reducing the risk of cissing and surface defects.

AD-AZ is supplied as part of the AQUAZINGA packaging and its use is optional, depending on application conditions and requirements.

PHYSICAL DATA AND TECHNICAL INFORMATION

WET PRODUCT

Density	1,00 kg/dm ³ (± 0,03 kg/dm ³) at 20°C
Appearance	Translucent white liquid

CONSERVATION

Shelf life	12 months, in the original, unopened packaging.
Storage	Store in a dry storage area between +5°C and +30°C.

PACKAGING

164 g	Available
-------	-----------

INSTRUCTIONS

For the production of 10 kg Aquazinga:

Gently swirl the bottle and add 164g of AD-AZ to the binder of Aquazinga while mixing. After one minute of thoroughly mixing, the powder can be added.

For the production of 20 kg Aquazinga:

Gently swirl the bottles and add 328g (2x 164g) of AD-AZ to the binder of Aquazinga while mixing. After one minute of thoroughly mixing, the powder can be added.

HEALTH & SAFETY

Always wear appropriate personal protective equipment (PPE) such as gloves and goggles.

For detailed information about the health and safety hazards and precautions for use, refer to the AD-AZ safety data sheet.

For more specific and detailed recommendations concerning the application of AD-AZ, please contact the Zingametal representative / distributor.

The information on this sheet is merely indicative and is given to the best of our knowledge based on practical experience and testing. The conditions or methods of handling, storage, use or disposal of the product cannot be controlled by us and are therefore outside our responsibility. For these and other reasons we retain no liability in case of loss, damage or costs that are caused by or that are linked in any way to the handling, storage, use or disposal of the product. Any claim concerning deficiencies must be made within 15 days upon reception of the goods quoting the relevant batch number. We retain the right to change the formula if properties of the raw material are changed. This data sheet replaces all former specimens.